

# PrintKote® C2S-LC

PRODUCT GUIDE

## Strength and printability in a recyclable solution.

Today's consumers want recyclable packaging for their food — without sacrificing performance. Both durable and recyclable, PrintKote® C2S-LC is also highly printable, making it a proven solution for ice cream bricks and other food applications.

### Features

- Reliable uniformity
- Smooth surface
- Classic bright-white styling without the use of optical brightening agents (OBA)
- Light backside coating
- Multiple caliper options available

### Benefits

- Delivers efficiency on converting and filling equipment
- Provides consistent ink holdout for strong printability and brand image consistency
- Offers fade resistance
- Provides consistent holdout performance
- Offers versatility for a variety of food applications

## Additional product information

### Sustainability

- Recyclable.
- All Smurfit Westrock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your Smurfit Westrock sales representative for certified fiber availability for this product.
- Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCCOC-6S751, FSC Company Code: FSC-C104002.

### Quality

- Produced at an ISO 9001 certified facility.

### Environmental and Product Safety

- Notices under US California Proposition 65 and the EU REACH regulation are not required.
- Elemental chlorine free (ECF) bleached fiber.
- Meets heavy metal limits of the US Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.

### Food Contact

- Meets multiple national requirements for food contact packaging, e.g., US and Canada. Contact your sales representative for information on specific markets and end uses.

### Applications

- Food packaging
- Foodservice
- Ice cream bricks

### Product classification

- Solid Bleached Sulfate
- SBS Paperboard
- CZ

Grade availability and typical board properties (U.S.)

Grade availability by caliper				Units	Method	
Caliper (pts)		0.020	0.022	0.024	inches	T-411
Nominal basis weight		224	242	257	lbs/3000 sqft	T-410
Moisture content		6.0	6.0	6.0	percent	T-412
ZDT		39	39	38	psi	T-541
Stiffness						
Taber 15°	MD	315	395	495	gf-cm	T-489
	CD	145	185	230	gf-cm	T-489
GE Brightness		86	86	86	percent	T-452
Smoothness						
Parker Print		1.3	1.3	1.3	µm	T-555
Color						
Hunter	b	1.5	1.5	1.5	L-a-b	T-524

Values are subject to change without notice.

For more information, please contact your Smurfit Westrock representative or visit our website at [westrock.com/printkote](https://westrock.com/printkote).

The information contained in this Product Guide is accurate to the best of Smurfit Westrock’s knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. Smurfit Westrock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

All Smurfit Westrock North American mills are ISO registered and certified to the SFI®, PEFC™, and FSC™ Chain of Custody Standards.

©2025 Smurfit Westrock and/or its affiliates. Smurfit Westrock and the Smurfit Westrock logo are trademarks owned by Smurfit Westrock and/or its affiliates. All rights reserved. 06/2025.

